


**FLOOR
GRES**

Information about collection:


ECOTECH naturale

|  | |
|--|--|
| FLORIM CERAMICHE S.p.A. Via Canaletto, 24 – 41042 Fiorano Modenese (MO) – Italia | |
| 06 | |
| EN 14411 Ceramic tiles, dry pressed, for internal and external floors and walls. | |
| Characteristics | Performance declarations |
| Reaction to fire | A1 - A1fl |
| Flexural tensile (breaking) strength | Breaking strength (N) > 1300 Modulus of rupture (N/mm ²) > 35 |
| Slipperiness | DM 236/89: > 0,4 DIN51130: R9 |
| Skid resistance | N.P.D. |
| Bond strength/adhesion | N.P.D. |
| Durability: Freeze/thaw cycle | Resistant |
| Resistance to thermal shock | Resistant |
| Release of dangerous substances: - release of cadmium - release of lead | N.P.D. N.P.D. |



Information about collection:

ECOTECH strutturato

|  | |
|--|--|
| <p>FLORIM CERAMICHE S.p.A. Via Canaletto, 24 – 41042 Fiorano Modenese (MO) – Italia</p> | |
| <p>06</p> | |
| <p>EN 14411</p> <p>Ceramic tiles, dry pressed, for internal and external floors and walls.</p> | |
| Characteristics | Performance declarations |
| Reaction to fire | A1 - A1fl |
| Flexural tensile (breaking) strength | Breaking strength (N) > 1300 Modulus of rupture (N/mm ²) > 35 |
| Slipperiness | DM 236/89: > 0,4 DIN51130: R11 |
| Skid resistance | N.P.D. |
| Bond strength/adhesion | N.P.D. |
| Durability: Freeze/thaw cycle | Resistant |
| Resistance to thermal shock | Resistant |
| Release of dangerous substances: - release of cadmium - release of lead | N.P.D. N.P.D. |