


**FLOOR
GRES**

Information about collection:


GLOBE bocciardato

	
FLORIM CERAMICHE S.p.A. Via Canaletto, 24 – 41042 Fiorano Modenese (MO) – Italia	
05	
EN 14411 Ceramic tiles, dry pressed, for internal and external floors and walls.	
Characteristics	Performance declarations
Reaction to fire	A1 - A1fl
Flexural tensile (breaking) strength	Breaking strength (N) > 1300 Modulus of rupture (N/mm ²) > 35
Slipperiness	DM 236/89: > 0,4 DIN51130: R11
Skid resistance	N.P.D.
Bond strength/adhesion	N.P.D.
Durability: Freeze/thaw cycle	Resistant
Resistance to thermal shock	Resistant
Release of dangerous substances: - release of cadmium - release of lead	N.P.D. N.P.D.



Information about collection:


GLOBE levigato

	
FLORIM CERAMICHE S.p.A. Via Canaletto, 24 – 41042 Fiorano Modenese (MO) – Italia	
05	
EN 14411 "Ceramic tiles dry pressed for internal floors and internal and external walls.	
Characteristics	Performance declarations
Reaction to fire	A1 - A1fl
Flexural tensile (breaking) strength	Breaking strength (N) > 1300 Modulus of rupture (N/mm ²) > 35
Slipperiness	DM 236/89: N.P.D. DIN51130: N.P.D.
Bond strength/adhesion	N.P.D.
Durability: Freeze/thaw cycle	Resistant
Resistance to thermal shock	Resistant
Release of dangerous substances: - release of cadmium - release of lead	N.P.D. N.P.D.

**FLOOR
GRES**

Information about collection:

GLOBE naturale

	
FLORIM CERAMICHE S.p.A. Via Canaletto, 24 – 41042 Fiorano Modenese (MO) – Italia	
05	
EN 14411 Ceramic tiles, dry pressed, for internal and external floors and walls.	
Characteristics	Performance declarations
Reaction to fire	A1 - A1fl
Flexural tensile (breaking) strength	Breaking strength (N) > 1300 Modulus of rupture (N/mm ²) > 35
Slipperiness	DM 236/89: > 0,4 DIN51130: R9
Skid resistance	N.P.D.
Bond strength/adhesion	N.P.D.
Durability: Freeze/thaw cycle	Resistant
Resistance to thermal shock	Resistant
Release of dangerous substances: - release of cadmium - release of lead	N.P.D. N.P.D.